


## THREADED SWING CHECK VALVE



### JV-602

<b>Feature</b>	Screwed Cap, Swing-Type Disc, Integral Seat
<b>Port Bore</b>	Full Bore
<b>End</b>	NPT, BSPT, ISO-228 Thread
<b>Material</b>	S/S; EN10213-4:1.4408; ASTM A351-CF8M
<b>Pressure</b>	600 PSI (PN40)
<b>Testing</b>	According to API-598 (EN12266-1,2)
<b>Temp.</b>	-20°C to 200°C (-4°F to 392°F)

### MATERIAL LIST


NO	PART	MATERIAL
1	BODY	CF8M=1.4408
2	CAP	CF8M=1.4408
3	DISC	CF8M=1.4408
4	ROD	CF8M=1.4408
5	DISC NUT	S/S 316
6	PIN	ANSI 304
7	GASKET	PTFE
8	BOLT	ANSI 304

### DIMENSIONS (mm)

SIZE	L	H	WT (KG)
1/2"	60	41.5	0.29
3/4"	78	46	0.53
1"	84	49	0.69
1-1/4"	94	53.5	0.85
1-1/2"	104	58.5	1.20
2"	122	67	1.80
2-1/2"	153	105	3.50
3"	175	125	5.00

JV-602  
07

JV-602H



### JV-602H

<b>Feature</b>	Screwed Cap, Swing-Type Disc, Integral Seat
<b>Port Bore</b>	Full Bore
<b>End</b>	NPT, BSPT, ISO-228 Thread
<b>Material</b>	S/S; EN10213-4:1.4408; ASTM A351-CF8M
<b>Pressure</b>	PN16
<b>Testing</b>	According to API-598 (EN12266-1,2)
<b>Temp.</b>	-20°C to 200°C (-4°F to 392°F)



### MATERIAL LIST

NO	PART	MATERIAL
1	COVER	CF8M=1.4408
2	GASKET	PTFE
3	PIN	S/S 316
4	PLUG	S/S 316
5	DISC	CF8M=1.4408
6	BODY	CF8M=1.4408
7	GASKET	PTFE

### DIMENSIONS (mm)

SIZE	L	H	WT (KG)
1/2"	66	46	0.30
3/4"	81	54	0.48
1"	91	60	0.75
1-1/4"	106.5	72	1.15
1-1/2"	121	75	1.54
2"	142	82	2.54
2-1/2"	159	90	3.80
3"	190	104	5.90